

# CIL

## Compact Integrated Laser



### Main Advantages & Features

- Based on cutting-edge modern diode-pumped technology
- High repetition rate (up to 10 pps continuously)
- Eyesafe rangefinding
- Compact, lightweight, single LRU
- Designed and tested IAW-MIL-STD

### Applications

- As an integrated part of air defense weapon systems
- As a stand-alone unit for gunfire control systems
- As an integrated sight for EO payloads/clusters

## Compact Integrated Laser

### Technical Data

Transmitter type	Diode-pumped, Erbium glass
Output energy, min	1.54 $\mu\text{m}$ (eyesafe) 10 mJ (after 3 sec.)
Repetition rate	10 pps
Beam divergence	1.5 mRad, adjustable
Range	
- Minimum	100 m
- Maximum	20,000 m
- Accuracy	$\pm 5$ m
Target discrimination	30 m
Extinction ratio	45 dB @ 85% reflectivity at 500 m target
Receiver optical aperture	90 mm
False alarm rate	1%, max
Laser beam-mechanical interface boresight	3 mRad
Boresighting telescope	
- Magnification	x 3.6
- Boresight with the laser beam	0.5 mRad
Cooling	Air flow (internal fan)
Communication	RS-422
Power consumption	100 W, max
Power supply	22-29 VDC, MIL-STD-704D
Weight	6.1 kg
Dimensions (L x W x H), mm	375 x 150 x 102

